## NSN 5905-00-808-0546



	I 5905-00-808-0546 ecision Nonwire Wound Variable Resistor - Page 1 of 2
View On	line at https://aerobasegroup.com/nsn/5905-00-808-0546
Section	Quantity:
1	
Body St	yle:
Cylindric	al bushing mounted
Reliabili	ty Indicator:
Not esta	blished
Overall	Length:
Betweer	1.031 inches and 1.125 inches
Body Di	ameter:
Betweer	0.890 inches and 0.922 inches
Shaft Di	ameter:
Betweer	0.248 inches and 0.251 inches
Shaft Le	ength:
Betweer	0.594 inches and 0.656 inches
Mountin	g Bushing Length:
Betweer	0.484 inches and 0.516 inches
Body Le	ength:
Betweer	0.437 inches and 0.469 inches
Overall	Diameter:
1.274 inc	ches
Shaft St	yle:
Round,	slotted
Actuato	r Type:
Single sl	naft
Maximu	m Starting Torque:
6.00 incl	n-ounces
Maximu	m Stop Torque:
128.00 ii	nch-ounces

Nonturn Device Location:

At 9 oclock

**Nonturn Device Radius:** 

Between 0.422 inches and 0.454 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Locking bushing

## NSN 5905-00-808-0546

**Fiig:** A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
2.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 251.0 and 318.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/4 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No