NSN 5905-00-808-5996

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-808-5996 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.8740 inches and 1.8750 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** Between 1.865 inches and 1.875 inches **Undercut Width:** Between 0.0730 inches and 0.0830 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.484 inches and 0.500 inches **Body Length:** 1.000 inches **Mounting Lip Diameter:** Between 1.9950 inches and 2.0050 inches **Mounting Lip Depth:** 0.0730 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 340.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.80 inch-ounces

0.80 inch-ounces
Shaft End Play:
0.002 inches
Shaft Runout:
0.001 inches

NSN 5905-00-808-5996

Precision Wire Wound Variable Resistor - Page 2 of 2



Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.00200 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.12/+0.12 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0