

NSN 5905-00-808-7371 Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-808-7371 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.126 inches **Body Diameter:** Between 0.484 inches and 0.516 inches **Shaft Diameter:** Between 0.124 inches and 0.126 inches **Shaft Length:** 0.438 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.453 inches

Overall Diameter:

Between 0.484 inches and 0.516 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Maximum Stop Torque:

64.00 inch-ounces

Nonturn Device Location:

At 4'30 oclock and at 10'30 oclock

Nonturn Device Radius:

Between 0.240 inches and 0.250 inches

Mechanical Backlash In Deg Angular Rotation:

3.0

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

NSN 5905-00-808-7371

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:	
Locking bushing	
Electrical Resistance Per Section:	
10.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
295.0	
Resistance Tempurature Characteristic Range Per Section In Percent:	
-0.0/+7.0 -55 degrees celsius single section and -0.0/+3.5 -25 degrees celsius single section and -0.0/+2.0 0 degrees celsius single sec	ctio
and -0.0/+0.0 25 degrees celsius single section and -2.5/+2.5 85 degrees celsius single section and -0.0/+5.5 120 degrees celsius single	le
section and -0.0/+8.5 150 degrees celsius single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
120.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
F single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	