NSN 5905-00-808-7471

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-808-7471

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.086 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.062 inches
Body Length:
Between 1.234 inches and 1.266 inches
Body Width:
Between 0.270 inches and 0.290 inches
Body Height:
Between 0.296 inches and 0.329 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
100.0 ohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-0.2/+0.2 single section
Ambient Tempurature In Dea Calsius Per Section At Full Pated Power:

70.0 single section

NSN 5905-00-808-7471

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Special Features:
Sst ams 5687 0.024 in. Maximum diameter wire @w/0.020 maximum r brazed in screwdriver slot of actuator
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No