Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-809-0664

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.063 inches

Body Diameter:

1.062 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.188 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

50.0 percent, rated amperes c and better finish

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

180.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections



Resistance Tolerance Per Section In Percent: -10.0/+10.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0