NSN 5905-00-809-4788

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-809-4788

Out to Out the
Section Quantity:
2
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Contact Arm Electrical Off Position:
Fully cw
Actuator Type:
Single shaft
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Double pole, single throw, normally open
End Application:
General purpose electronic test equipment
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
250.0 ohms all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:

N/a

NSN 5905-00-809-4788

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0