## NSN 5905-00-809-4788

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-809-4788

| Out to Out the                                 |
|--|
| Section Quantity:                              |
| 2  |
| Reliability Indicator:                         |
| Not established                                |
| Shaft Diameter:                                |
| 0.250 inches                                   |
| Shaft Length:                                  |
| 0.500 inches                                   |
| Shaft Style:                                   |
| Round, slotted                                 |
| Switch Type:                                   |
| Rotary   |
| Contact Arm Electrical Off Position:           |
| Fully cw                                       |
| Actuator Type:                                 |
| Single shaft                                   |
| Switch Operating Position:                     |
| Start of rotation                              |
| Switch Contact Arrangement:                    |
| Double pole, single throw, normally open       |
| End Application:                               |
| General purpose electronic test equipment      |
| Screw Thread Diameter:                         |
| 0.375 inches                                   |
| Screw Thread Series Designator:                |
| Unef   |
| Screw Thready Qty Per Inch (tpi):              |
| 32.0   |
| Mounting Method:                               |
| Standard bushing                               |
| Electrical Resistance Per Section:             |
| 250.0 ohms all sections                        |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air all sections                      |
| Resistance Tolerance Per Section In Percent:   |
| -10.0/+10.0 all sections                       |
| Standard Taper Curve Per Section:              |
| A all sections                                 |
| Terminal Type And Quantity:                    |
| 6 tab, solder lug                              |
| Shelf Life:                                    |

N/a

## NSN 5905-00-809-4788

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



|   |     | • - |    |     |    |    |    |    |
|---|-----|-----|----|-----|----|----|----|----|
|   | In  |     | Of | RЛ  | മാ | CI | ır | Δ. |
| L | ,,, |     |    | IVI | ca |    |    |    |

--

Demilitarization:

No

Fiig:

A002a0