

View Online at <https://aerobasegroup.com/nsn/5905-00-809-6475>

Electrical Resistance:

500.0 kilohms and 100.0 kilohms and 25.0 kilohms and 40.0 kilohms and 50.0 kilohms and 10.0 kilohms and 5.0 kilohms

Resistance Tolerance In Percent:

-10.0/+10.0 and -5.0/+5.0 and -5.0/+5.0 and -5.0/+5.0 and -5.0/+5.0 and -10.0/+10.0 and -10.0/+10.0

Resistor Power Dissipation Rating In Watts:

0.5 and 1.0 and 1.0 and 1.0 and 1.0 and 1.0 and 1.0

Mounting Method:

Holes

Component Quantity:

1 and 2 and 1 and 1 and 1 and 1 and 2

Mounting Configuration:

Two 0.187 in. Diameter holes 1.375 in. C to c

Component Controlling Agency:

Allen bradley co., dale products inc, dale products inc, dale products inc, bourns laboratories inc, bourns laboratories inc, bourns laboratories inc

Component Name:

Variable composition resistor, variable wire wound resistor, variable wire wound resistor, variable wire wound resistor, variable wire wound resistor, variable wire wound resistor, variable wire wound resistor

Component Identifying Number:

G type no. And a10--w-100kl part no. And 10-w-25kl part no. And a10-2-40kl part no. And 220l-403-203 part no. And 220l-403-103 part no. And 220l-403-402 part no.

Assembly Construction Method:

Stack, 5 stacks, 2 through bolts per stack, 1on two through bolts, 1 on bracket

Component Relationship:

Not matched

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T172-f