Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-809-8454

# Section Quantity:

1

Body Style:

Cylindrical hole/slot mounted

# **Reliability Indicator:**

Not established

**Overall Length:** 

4.457 inches

#### First Flat Length:

1.500 inches

Flat Height:

0.344 inches

#### **Body Diameter:**

6.090 inches

Shaft Diameter:

0.375 inches

Shaft Length:

Between 0.375 inches and 0.376 inches

## Mounting Bushing Length:

0.375 inches

### Body Length:

2.410 inches

## **Overall Diameter:**

6.810 inches

### Mounting Hole/stud Circle Diameter:

2.380 inches

## Shaft Style:

Round, flatted

### Actuator Type:

Single shaft

### Maximum Starting Torque:

160.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

### Nonturn Device Location:

At 3 oclock and at 9 oclock

# Screw Thread Diameter:

0.250 inches

# Screw Thread Series Designator:

Unc

### Screw Thready Qty Per Inch (tpi):

20.0

# NSN 5905-00-809-8454

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Mounting Facility Quantity:** 

2

## Terminal Location:

Radially positioned over less than half the circumference

#### **Mounting Method:**

Threaded hole

**Electrical Resistance Per Section:** 

150.0 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 310.0 and 325.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

390.0 single section

Power Dissipation Rating Per Section In Watts:

300.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

# **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:** 

81349-mil-r-22/11 government specification

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A002a0