Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-810-0623

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.307 inches and 1.317 inches **Overall Height:** Between 0.275 inches and 0.285 inches **Overall Width:** Between 0.270 inches and 0.290 inches Mounting Hole Diameter: 0.125 inches Shaft Diameter: Between 0.109 inches and 0.141 inches Shaft Length: Between 0.047 inches and 0.078 inches **Body Length:** Between 1.245 inches and 1.255 inches **Body Width:** Between 0.270 inches and 0.290 inches **Body Height:** Between 0.275 inches and 0.285 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Maximum Starting Torque: 7.50 inch-ounces Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 20.0 kilohms single section

NSN 5905-00-810-0623

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

9000.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0