## NSN 5905-00-810-0648

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-810-0648

25.0/425.0 second temp coefficient Electrical Resistance: 1.393 kilohms Resistance Tolerance In Percent: -0.200/40.200 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/-25.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Style Designator: Avial terminal each end Test Data Document: Style Designator: Avial terminal each end Test Data Document: Style Designator: Avial terminal each end Test Data Scowering drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13/499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing) specification, standard or other document that may be referenced in a basic governing drawing) and 13/499-748-9629-00 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13/499-748-9629-00 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Demilitarization: No Demilitarization: No Filig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 1.393 kilohms Resistance Tolerance in Percent: -0.2004/-0.200 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0-25.0 temp range of first temp coefficient in Deg Celsius: -55.0-25.0 temp range of first temp coefficient in Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.125 inches Body Length: -0.250 inches Power Dissipation Rating in Watts: -0.250 inches Typese Power Dissipation Rating in Watts: -0.250 free air Style Designator: -Axial terminal each end Test Data Document: -13499-748-955-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing).	
1.393 kilohms Resistance Tolerance In Percent: -0.200/40.200 Ambient Tempurature In Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0v.25.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.125 inches Body Length: -0.250 inches Power Dissipation Rating In Watts: -0.250 inches Fower Dissipation Rating In Watts: -0.250 inches	·
Resistance Tolerance In Percent: -0.200/40.200 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-25.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In Deg Celsius: -56.0f-26.0 temp range of first temp coefficient In	
-0.200/+0.200 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/-25.0 temp range of first temp coefficient In Deg Celsius: -55.0/-25.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.255 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/-25.0 temp range of first temp coefficient Inclosure Method: Encapsulated  Terrinial Type:  Wire lead  Reliability Indicator: Not established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.026 ree air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Na  Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/-25.0 temp range of first temp coefficient Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Not established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating in Watts: 0.025 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Na  Unit Of Measure:   Demilitarization:  No  Flig:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/-25.0 temp range of first temp coefficient InClosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating in Watts: 0.250 inches  Power Dissipation Rating in Watts: 0.250 fire air  Style Designator:  Axial terminal each end  Test Data Document:  13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.01-25.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.25 free air Style Designator: Axial terminal each end Test Data Document: 14399-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/-25.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.025 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing trawing, original equipment manufacturer drawing, specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Filig:	
-55.0/-25.0 temp range of first temp coefficient  Inclosure Method: Encapsulated Torminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.025 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0,125 inches Body Length: 0,250 inches Power Dissipation Rating In Watts: 0,025 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.026 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9529-00 drawing (this is the basic governing drawing, such as a contractor drawing) and 13499-748-9529-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.025 free air  Style Designator: Axial terminal each end Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Flig:	
Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.025 free air  Style Designator:  Axial terminal each end  Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	
Reliability Indicator:  Not established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.025 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Note established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.025 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Body Diameter:  0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.025 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Filig:	
0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.025 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	
Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.025 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fig:	
0.250 inches  Power Dissipation Rating In Watts: 0.025 free air  Style Designator:  Axial terminal each end  Test Data Document: 13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fitig:	
Power Dissipation Rating In Watts:  0.025 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
0.025 free air  Style Designator: Axial terminal each end  Test Data Document:  13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Style Designator:  Axial terminal each end  Test Data Document:  13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
Axial terminal each end  Test Data Document:  13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
Test Data Document:  13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
13499-748-9555-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-9629-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No  Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0