

View Online at <https://aerobasegroup.com/nsn/5905-00-810-1865>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.4330 inches and 0.4430 inches

**Pilot Length:**

Between 0.0570 inches and 0.0670 inches

**Overall Length:**

1.375 inches

**Undercut Diameter:**

Between 0.433 inches and 0.443 inches

**Undercut Width:**

Between 0.0570 inches and 0.0670 inches

**Body Diameter:**

Between 0.484 inches and 0.516 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

Between 0.547 inches and 0.578 inches

**Body Length:**

1.375 inches

**Overall Diameter:**

Between 0.484 inches and 0.516 inches

**Mounting Lip Diameter:**

Between 0.4840 inches and 0.5160 inches

**Mounting Lip Depth:**

Between 0.0570 inches and 0.0670 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

300.0

**Maximum Starting Torque:**

3.00 inch-ounces

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

20.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Power Dissipation Rating Per Section In Watts:**

4.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

30.0 deg. Mech. Overtravel

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0