NSN 5905-00-810-2179

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-810-2179

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.109 inches
First Flat Length:
0.375 inches
Flat Height:
0.094 inches
Body Diameter:
0.734 inches
Shaft Diameter:
0.125 inches
Shaft Length:
1.250 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.438 inches
Overall Diameter:
0.969 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.0 kilohms single section
Power Dissipation Rating Per Section In Watts:

0.5 free air single section

NSN 5905-00-810-2179

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/o

Demilitarization:

Unit Of Measure:

No

Fiig:

A002a0