## NSN 5905-00-810-4916

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-810-4916

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 1.292 inches and 1.334 inches
Overall Height:
Between 0.797 inches and 0.828 inches
Overall Width:
Between 0.270 inches and 0.290 inches
Mounting Hole Diameter:
0.086 inches
Shaft Diameter:
Between 0.109 inches and 0.141 inches
Shaft Length:
Between 0.047 inches and 0.079 inches
Body Length:
Between 1.245 inches and 1.255 inches
Body Width:
Between 0.270 inches and 0.290 inches
Body Height:
Between 0.797 inches and 0.828 inches
Shaft Style:
Round, slotted
Contact Arm Electrical Off Position:
Fully ccw-cw
Actuator Type:
Single shaft
Maximum Starting Torque:
7.50 inch-ounces
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
500.0 ohms single section

## NSN 5905-00-810-4916

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila: