NSN 5905-00-810-5312

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-810-5312

Section Quantity:
2
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Features Provided:
Grounded contact arm and nonmetallic shaft
Electrical Resistance Per Section:
300.000 ohms 1st section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:

Stops

NSN 5905-00-810-5312

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0