Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-811-4379

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.420 inches and 1.520 inches **Overall Height:** Between 0.290 inches and 0.330 inches **Overall Width:** Between 0.170 inches and 0.200 inches **Mounting Hole Diameter:** 0.086 inches Shaft Diameter: Between 0.105 inches and 0.130 inches Shaft Length: Between 0.040 inches and 0.080 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.170 inches and 0.200 inches **Body Height:** Between 0.290 inches and 0.330 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Maximum Starting Torque:** 5.00 inch-ounces Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 7.8 kilohms single section **Rotary Actuator Travel In Angular Deg:**

7920.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0/+70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire loop Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0