NSN 5905-00-811-7114

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-811-7114 **Section Quantity:**

2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 1.985 inches and 2.047 inches **Body Diameter:** 1.812 inches **Shaft Diameter:** Between 0.249 inches and 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** Between 1.172 inches and 1.234 inches **Overall Diameter:** 1.812 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 1080.0 and 1084.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.005 inches

Shaft Runout:

0.00005 inches

Lateral Runout:

0.003 inches

NSN 5905-00-811-7114

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.004 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 ohms c and better finish
Rotary Actuator Travel In Angular Deg:
Between 1080.0 and 1084.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 all sections
Power Dissipation Rating Per Section In Watts:
3.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 2nd section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 1st section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-811-7114

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0