NSN 5905-00-811-7469

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-811-7469

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 0.703 inches and 0.797 inches
Body Diameter:
Between 0.719 inches and 0.781 inches
Shaft Diameter:
Between 0.124 inches and 0.126 inches
Shaft Length:
Between 0.344 inches and 0.406 inches
Mounting Bushing Length:
Between 0.234 inches and 0.266 inches
Body Length:
Between 0.359 inches and 0.391 inches
Overall Diameter:
0.953 inches
Shaft Style:
Round, slotted
Round, slotted Actuator Type:
•
Actuator Type:
Actuator Type: Single shaft
Actuator Type: Single shaft Maximum Starting Torque:
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque:
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location:
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 9 oclock
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius:
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.359 inches and 0.391 inches
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.359 inches and 0.391 inches Screw Thread Diameter:
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.359 inches and 0.391 inches Screw Thread Diameter: 0.250 inches
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.359 inches and 0.391 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator:
Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.359 inches and 0.391 inches Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef

Mounting Method:Standard bushing

Radially positioned over less than half the circumference

NSN 5905-00-811-7469

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 295.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
31349-mil-r-94/2 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fila: