NSN 5905-00-811-7471



View Online at ht	tps://aerobasegroup.com/nsn/5905-00-811-7471
Section Quantity	<i>y</i> :
1	
Body Style:	
Cylindrical bushir	ng mounted
Reliability Indica	ator:
Not established	
Overall Length:	
Between 0.703 ir	ches and 0.797 inches
Body Diameter:	
Between 0.719 ir	ches and 0.781 inches
Shaft Diameter:	
Between 0.124 ir	ches and 0.126 inches
Shaft Length:	
Between 0.344 ir	ches and 0.406 inches
Mounting Bushi	ng Length:
Between 0.234 ir	ches and 0.266 inches
Body Length:	
Between 0.359 ir	ches and 0.391 inches
Overall Diamete	r:
0.953 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Maximum Starti	ng Torque:
6.00 inch-ounces	
Maximum Stop	Forque:
80 00 inch-ounce	e e

80.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.359 inches and 0.391 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-811-7471

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:		
25.000 kilohms single section		
Rotary Actuator Travel In Angular Deg:		
Between 295.0 and 305.0		
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:		
120.0 single section		
Power Dissipation Rating Per Section In Watts:		
0.5 free air single section		
Resistance Tolerance Per Section In Percent:		
-10.0/+10.0 single section		
Actuator Travel Control Feature:		
Stops		
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:		
70.0 single section		
Standard Taper Curve Per Section:		
A single section		
Test Data Document:		
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;		
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental		
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).		
Terminal Type And Quantity:		
3 tab, solder lug		
Specification Data:		
81349-mil-r-94/2 government specification		
Shelf Life:		
N/a		
Unit Of Measure:		
		
Demilitarization:		
No		