

View Online at <https://aerobasegroup.com/nsn/5905-00-811-8319>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

Between 3.250 inches and 3.406 inches

Body Diameter:

Between 1.657 inches and 1.719 inches

Shaft Diameter:

Between 0.248 inches and 0.252 inches

Shaft Length:

Between 1.969 inches and 2.031 inches

Mounting Bushing Length:

Between 0.359 inches and 0.391 inches

Body Length:

Between 0.922 inches and 0.984 inches

Overall Diameter:

Between 2.594 inches and 2.656 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 275.0 and 285.0

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

50.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 295.0 and 305.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0