## NSN 5905-00-811-8320

**Section Quantity:** 

3 wire lead

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-811-8320

•
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
Between 0.245 inches and 0.255 inches
Body Diameter:
Between 0.245 inches and 0.255 inches
Body Length:
Between 0.245 inches and 0.255 inches
Overall Diameter:
Between 0.245 inches and 0.255 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:

## NSN 5905-00-811-8320

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
D !!!!! !!

Demilitarization:

No

Fiig:

A002a0