## NSN 5905-00-811-9145

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-811-9145

Electrical Resistance: 5.110 kilohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.250 inches  Body Length: 0.344 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Axial terminal each end  Test Data Document:
S.110 kilohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead Reliability Indicator: Not established  Body Diameter: 0.250 inches  Body Length: 0.344 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Axial terminal each end
Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.344 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.344 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.344 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end
Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.250 inches  Body Length: 0.344 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Axial terminal each end
Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.250 inches  Body Length: 0.344 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end
Reliability Indicator: Not established  Body Diameter: 0.250 inches  Body Length: 0.344 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Axial terminal each end
Not established  Body Diameter:  0.250 inches  Body Length:  0.344 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end
Body Diameter:  0.250 inches  Body Length:  0.344 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end
0.250 inches  Body Length: 0.344 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end
Body Length:  0.344 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end
0.344 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end
Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end
0.125 free air  Style Designator:  Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Test Data Document:
81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0