Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-812-4562

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### Reliability Indicator:

Not established

### **Body Diameter:**

0.500 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.500 inches

### Mounting Bushing Length:

0.375 inches

### Body Length:

0.550 inches

### Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

340.0

### Nonturn Device Location:

At 12 oclock

### Nonturn Device Radius:

0.157 inches

### Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# Mounting Method:

Locking bushing

# **Features Provided:**

Nonmetallic shaft

# **Electrical Resistance Per Section:**

500.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

340.0



#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

### **Actuator Travel Control Feature:**

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

### Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

3 tab, solder lug

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

### Fiig:

A002a0