## NSN 5905-00-812-4971

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-812-4971

-500.0/+500.0   Electrical Resistance: 2.610 kilohms   Resistance Tolerance in Percent: -1.000/+1.000   Ambient Tompurature in Deg Celsius At Full Rated Power: -1.00   Ambient Tompurature in Deg Celsius At Full Rated Power: -1.000   Ambient Tompurature in Deg Celsius At Even Percent Rated Power: -1.000   Ambient Tompurature in Deg Celsius At Zero Percent Rated Power: -1.000   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature Range Of Tompurature Coefficient in Deg Celsius: -1.50.04   Tompurature	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 2.510 kilohims Resistance Tolerance in Percent: -1.000/4-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 160.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/4-105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Resistance: 0.156 inches Body Diameter: 0.156 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.128 free air Special Features: 100 pet radiographic inspection x-ray with each item Style Designator: 4.154 Designator: 5.155 Data Document: 94758-43-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit of Measure: - Domilitarization: No Filig:	
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 160.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.156 inches Body Length: 0.281 inches Power Diasipation Rating In Watts: 0.125 free air Special Features: 10.126 free air Special Features: 10.126 inches Ad-3-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+ 105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.156 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Special Features: 100 pct radiographic inspection x-ray with each item Style Designator: Axial terminal each end Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	2.610 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 160.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.156 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.125 fee air Special Features: 100 pct radiographic inspection x-ray with each item Style Designator: Axial terminal each end Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shell Life: Na Unit Of Measure: - Demilitarization: No Figi:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  180.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.156 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 fee air Special Features: 100 pet radiographic inspection x-ray with each item Style Designator: Axial terminal each end Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  180.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0  Horicolsure Method: Hermetically sealed  Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.156 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Special Features: 100 pct radiographic inspection x-ray with each item Style Designator: Axial terminal each end  Tests Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.156 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Special Features: 100 pct radiographic inspection x-ray with each item Style Designator: Axial terminal each end Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.156 inches Body Length: 0.281 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Special Features: 100 pct radiographic inspection x-ray with each item Style Designator: Axial terminal each end Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Via Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+105.0 Inclosure Method: Hermetically sealed Torminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.156 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.125 free air Special Features: 100 pct radiographic inspection x-ray with each item Style Designator: Axial terminal each end Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	160.0
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.156 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.125 free air Special Features: 100 pct radiographic inspection x-ray with each item Style Designator: Axial terminal each end Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Hermetically sealed  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.156 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Special Features: 100 pct radiographic inspection x-ray with each item  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: Na  Unit Of Measure:  Demilitarization: No  Fig:	-55.0/+105.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.156 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Special Features: 100 pct radiographic inspection x-ray with each item  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Inclosure Method:
Wire lead  Reliability Indicator: Not established  Body Diameter: 0.156 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Special Features: 100 pct radiographic inspection x-ray with each item  Style Designator: Axial terminal each end Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Fig:	Hermetically sealed
Reliability Indicator: Not established  Body Diameter: 0.156 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Special Features: 100 pct radiographic inspection x-ray with each item  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Not established  Body Diameter: 0.156 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Special Features: 100 pct radiographic inspection x-ray with each item  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter:  0.156 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.125 free air  Special Features:  100 pct radiographic inspection x-ray with each item  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Reliability Indicator:
0.156 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Special Features: 100 pct radiographic inspection x-ray with each item  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Not established
Body Length:  0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Special Features: 100 pct radiographic inspection x-ray with each item  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.281 inches  Power Dissipation Rating In Watts: 0.125 free air  Special Features: 100 pct radiographic inspection x-ray with each item  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fig:	0.156 inches
Power Dissipation Rating In Watts:  0.125 free air  Special Features: 100 pct radiographic inspection x-ray with each item  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Body Length:
0.125 free air  Special Features:  100 pct radiographic inspection x-ray with each item  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.281 inches
Special Features:  100 pct radiographic inspection x-ray with each item  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Power Dissipation Rating In Watts:
100 pct radiographic inspection x-ray with each item  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.125 free air
Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Special Features:
Axial terminal each end  Test Data Document:  94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	100 pct radiographic inspection x-ray with each item
Test Data Document:  94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Style Designator:
94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	94756-443-0001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	<del></del>
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0