NSN 5905-00-813-2233

Section Quantity:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-813-2233

2
Reliability Indicator:
Not established
Body Diameter:
0.969 inches
Shaft Diameter:
0.265 inches
Shaft Length:
2.187 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.875 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better industrial clears
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 all sections
Standard Taper Curve Per Section:
L all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:

NSN 5905-00-813-2233

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0