NSN 5905-00-813-4156

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-813-4156 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.8740 inches and 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 4.986 inches **Undercut Diameter:** 1.812 inches **Undercut Width:** Any acceptable **Body Diameter:** 1.825 inches **Mounting Hole Diameter:** 0.164 inches **Angle Of Mounting Hole In Deg:** 60.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.906 inches and 0.969 inches **Body Length:** 4.048 inches **Overall Diameter:** 2.300 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0930 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches **Shaft Style:** Round

Shaft Bearing Type:

Ball

NSN 5905-00-813-4156

Precision Wire Wound Variable Resistor - Page 2 of 3



Actuator Type: Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 1.50 inch-ounces **Maximum Stop Torque:** 480.00 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.001 inches **Pilot Diameter Runout:** 0.001 inches **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 10.0 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 3780.0 **Function Conformity Tolerance Per Section:** -0.05/+0.05 2nd section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 all sections **Power Dissipation Rating Per Section In Watts:** 5.0 free air all sections **Function Conformity Per Section:** All sections independent linearity **Fixed Tap Quantity Per Section:** 2 1st section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections

Stops

Actuator Travel Control Feature:

NSN 5905-00-813-4156

Precision Wire Wound Variable Resistor - Page 3 of 3



Function Characteristic Per Section:

All sections linear

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-25.0/+25.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0