## NSN 5905-00-813-5584

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-813-5584

Section Quantity:
1
Overall Length:
1.140 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.250 inches
Overall Diameter:
1.812 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
1080.0
Maximum Starting Torque:
1.80 inch-ounces
Maximum Running Torque:
1.30 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.000 kilohms single section
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section

## NSN 5905-00-813-5584

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal	Type An	d Quantity:

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0