NSN 5905-00-813-5807



NSN 5905-00-813-5807 Precision Wire Wound Variable Resistor - Page 1 of 2	AG
View Online at https://aerobasegroup.com/nsn/5905-00-813-5807	
Section Quantity:	
1	
Body Style:	
Rectangular w/bushing	
Reliability Indicator:	
Not established	
Overall Length:	
Between 2.610 inches and 2.766 inches	
Shaft Diameter:	
Between 0.248 inches and 0.250 inches	
Shaft Length:	
Between 0.907 inches and 0.969 inches	
Mounting Bushing Length:	
Between 0.344 inches and 0.406 inches	
Body Length:	
Between 1.531 inches and 1.593 inches	
Body Width:	
Between 0.859 inches and 0.891 inches	
Body Height:	
Between 0.984 inches and 1.016 inches	
Overall Diameter:	
Between 0.859 inches and 0.891 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular Rotation:	
Between 3590.0 and 3610.0	
Maximum Starting Torque:	
3.00 inch-ounces	

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Maximum Stop Torque:

50.00 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

Between 0.422 inches and 0.454 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

NSN 5905-00-813-5807

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 3590.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section absolute linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0