NSN 5905-00-813-5911

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-813-5911

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Rectangular w/mounting holes/slots |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| Between 1.300 inches and 1.340 inches |
| Terminal Length: |
| Between 0.469 inches and 0.531 inches |
| Overall Height: |
| Between 0.769 inches and 0.861 inches |
| Overall Width: |
| Between 0.180 inches and 0.200 inches |
| Mounting Hole Diameter: |
| 0.093 inches |
| Shaft Diameter: |
| Between 0.100 inches and 0.130 inches |
| Shaft Length: |
| Between 0.060 inches and 0.080 inches |
| Body Length: |
| Between 1.240 inches and 1.260 inches |
| Body Width: |
| Between 0.180 inches and 0.200 inches |
| Body Height: |
| Between 0.300 inches and 0.330 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Maximum Starting Torque: |
| 8.00 inch-ounces |
| Center To Center Distance Between Terminals: |
| Between 0.890 inches and 0.910 inches |
| Lateral Distance Between Mounting Hole Centers: |
| Between 0.890 inches and 0.910 inches |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Rear-bottom |
| |

Mounting Method:

Terminal and unthreaded hole

NSN 5905-00-813-5911

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Center To Center Distance Between Terminal Rows: |
|--|
| 0.700 inches |
| Features Provided: |
| Nonmetallic shaft |
| Electrical Resistance Per Section: |
| 500.0 kilohms single section |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| Between 0.190 inches and 0.210 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -250.0/+250.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.75 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Test Data Document: |
| 81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 pin |
| Specification Data: |
| 81349-mil-r-22097/2 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Δ002=0 |