Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-814-4988

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

1.094 inches

### Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

### Mounting Bushing Length:

0.500 inches

### Body Length:

### 0.562 inches

Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

Between 309.0 and 320.0

## Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# **Mounting Method:**

Locking bushing

# **Electrical Resistance Per Section:**

35.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

# Resistance Tempurature Characteristic Range Per Section In Percent:

-3.0/+0.0 -55 degrees celsius single section and -5.0/+10.0 -25 degrees celsius single section and -5.0/+10.0 25 degrees celsius single



### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

#### **Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

3 tab, solder lug

#### **Specification Data:**

81349-mil-r-94/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A002a0