

View Online at <https://aerobasegroup.com/nsn/5905-00-814-5035>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Not established

**Overall Length:**

1.213 inches

**Terminal Length:**

0.500 inches

**Overall Height:**

0.812 inches

**Overall Width:**

0.359 inches

**Mounting Hole Diameter:**

0.086 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.062 inches

**Body Length:**

1.250 inches

**Body Width:**

0.250 inches

**Body Height:**

0.312 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

7.50 inch-ounces

**Center To Center Distance Between Terminals:**

Between 0.690 inches and 0.710 inches

**Lateral Distance Between Mounting Hole Centers:**

1.000 inches

**Screw Thread Diameter:**

0.216 inches

**Screw Thread Series Designator:**

Unf

**Screw Thread Qty Per Inch (tpi):**

28.0

**Mounting Facility Quantity:**

2

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Unthreaded hole

**Center To Center Distance Between Terminal Rows:**

0.100 inches

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

Between 0.290 inches and 0.310 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

175.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0