NSN 5905-00-814-5035

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-814-5035

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Rectangular w/mounting holes/slots |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 1.213 inches |
| Terminal Length: |
| 0.500 inches |
| Overall Height: |
| 0.812 inches |
| Overall Width: |
| 0.359 inches |
| Mounting Hole Diameter: |
| 0.086 inches |
| Shaft Diameter: |
| 0.125 inches |
| Shaft Length: |
| 0.062 inches |
| Body Length: |
| 1.250 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 0.312 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Maximum Starting Torque: |
| 7.50 inch-ounces |
| Center To Center Distance Between Terminals: |
| Between 0.690 inches and 0.710 inches |
| Lateral Distance Between Mounting Hole Centers: |
| 1.000 inches |
| Screw Thread Diameter: |
| 0.216 inches |
| Screw Thread Series Designator: |
| Unf |
| Screw Thready Qty Per Inch (tpi): |
| 28.0 |

NSN 5905-00-814-5035

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Mounting Facility Quantity: |
|---|
| 2 |
| Terminal Location: |
| Lower adjacent side single row |
| Mounting Method: |
| Unthreaded hole |
| Center To Center Distance Between Terminal Rows: |
| 0.100 inches |
| Electrical Resistance Per Section: |
| 5.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 9000.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| Between 0.290 inches and 0.310 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 175.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -50.0/+50.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |