Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-815-0963

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 0.950 inches and 1.060 inches **Overall Height:** Between 0.305 inches and 0.325 inches **Overall Width:** 0.170 inches **Mounting Hole Diameter:** 0.086 inches Shaft Diameter: Between 0.109 inches and 0.141 inches Shaft Length: Between 0.040 inches and 0.060 inches **Body Length:** Between 0.984 inches and 1.016 inches **Body Width:** Between 0.160 inches and 0.180 inches **Body Height:** 0.315 inches Shaft Style: Round, slotted **Contact Arm Electrical Off Position:** Fully ccw Actuator Type: Single shaft Maximum Starting Torque: 5.00 inch-ounces Lateral Distance Between Mounting Hole Centers: Between 0.745 inches and 0.755 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 1.0 kilohms single section

NSN 5905-00-815-0963

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 5400.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

Power Dissipation Rating Per Section In Watts:

70.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

125.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0