NSN 5905-00-815-3693

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-815-3693 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** Between 0.719 inches and 0.781 inches **Shaft Diameter:** Between 0.124 inches and 0.126 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 1.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.2 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life:

N/a
Unit Of Measure:

NSN 5905-00-815-3693

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	\sim	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A002a0