NSN 5905-00-815-4656

Fiig: A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-815-4656

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -20.0/+20.0 Electrical Resistance: 89.800 kilohms Resistance Tolerance In Percent: -0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Electrical Resistance: 89.800 kilohms Resistance Tolerance In Percent: -0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Taminal Type: Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.662 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
89.800 kilohms Resistance Tolerance In Percent: -0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: -0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Not established Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Terminal Length: 0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
0.375 inches Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Body Diameter: 0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
0.562 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Body Length: 0.625 inches Power Dissipation Rating In Watts: 0.333 free air
0.625 inches Power Dissipation Rating In Watts: 0.333 free air
Power Dissipation Rating In Watts: 0.333 free air
0.333 free air
Terminal Width:
0.188 inches
Style Designator:
Radial terminal each end
Test Data Document:
81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-93/3 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: