NSN 5905-00-816-2489

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-816-2489 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.797 inches **Body Diameter:** 1.328 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.750 inches **Overall Diameter:** 1.375 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** Between 0.548 inches and 0.570 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:**

Rear end **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft

NSN 5905-00-816-2489

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
5.0 ohms single section
Rotary Actuator Travel In Angular Deg:
355.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0