

View Online at <https://aerobasegroup.com/nsn/5905-00-816-6618>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.0300 inches

Pilot Length:

0.0400 inches

Overall Length:

1.300 inches

Undercut Diameter:

1.030 inches

Undercut Width:

0.0600 inches

Body Diameter:

1.093 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.375 inches

Body Length:

0.925 inches

Overall Diameter:

1.340 inches

Mounting Lip Diameter:

1.0930 inches

Mounting Lip Depth:

0.0600 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

352.0

Maximum Starting Torque:

0.30 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 percent, rated amperes c and better industrial clears

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 2nd section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

160.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 all sections

Unpackaged Unit Weight:

1.70 ounces

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0