## NSN 5905-00-818-2353

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-818-2353

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.947 inches
Shaft Diameter:
0.249 inches
Shaft Length:
0.653 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.850 inches
Shaft Style:
Round
Actuator Type:
Dual concentric
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
1.30 inch-ounces
Maximum Running Torque:
0.90 inch-ounces
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
3610.0
<b>Function Conformity Tolerance Per Section:</b>

5.0 free air all sections

-0.10/+0.10 all sections

**Function Conformity Per Section:** 

**Power Dissipation Rating Per Section In Watts:** 

All sections independent linearity

## NSN 5905-00-818-2353

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section in Percent:
-5.0/+5.0 1st section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Terminal Type And Quantity:
14 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: