

View Online at <https://aerobasegroup.com/nsn/5905-00-818-2404>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.266 inches

Terminal Length:

0.297 inches

Body Diameter:

1.156 inches

Shaft Diameter:

Between 0.248 inches and 0.250 inches

Shaft Length:

Between 0.547 inches and 1.000 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.266 inches

Overall Diameter:

1.453 inches

Shaft Style:

Round

Actuator Type:

Dual concentric

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.516 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

3.0 percent, rated amperes c and better finish

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0