NSN 5905-00-818-2404

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-818-2404 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.266 inches **Terminal Length:** 0.297 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** Between 0.547 inches and 1.000 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.266 inches **Overall Diameter:** 1.453 inches **Shaft Style:** Round **Actuator Type:** Dual concentric **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.516 inches and 0.547 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:**

Standard bushing

Features Provided:

Nonmetallic shaft

NSN 5905-00-818-2404

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	ectrica	N D	ociet	anco	Dor	Sact	ion:
ᄗ	ectrica	31 K	esist	ance	rer	Seci	ion:

3.0 percent, rated amperes c and better finish

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0