NSN 5905-00-818-5917

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-818-5917

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.578 inches
Body Diameter:
0.970 inches
Shaft Diameter:
Between 0.245 inches and 0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.500 inches
Body Length:
1.578 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
300.0 kilohms single section
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Power Dissipation Rating Per Section In Watts:

5.5 free air single section

Function Conformity Per Section:

Single section independent linearity

NSN 5905-00-818-5917

No Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: