## NSN 5905-00-818-9756

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-818-9756 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.812 inches **Body Diameter:** 1.812 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** Between 0.781 inches and 0.843 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 2.000 inches **Overall Diameter:** 2.156 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Maximum Stop Torque:** 550.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.005 inches

**Shaft Runout:** 0.0005 inches

## NSN 5905-00-818-9756

**Lateral Runout:** 

Precision Wire Wound Variable Resistor - Page 2 of 3



0.003 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Stops
Stops Function Characteristic Per Section:
Stops  Function Characteristic Per Section:  Single section linear
Stops  Function Characteristic Per Section:  Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+130.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section
Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+130.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity:
Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -0.0/+130.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section

N/a

## NSN 5905-00-818-9756

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0