Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-819-0949

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# Body Diameter:

1.156 inches

## Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

### Mounting Bushing Length:

0.375 inches

Body Length:

#### 0.625 inches

Shaft Style:

#### Round, slotted

Actuator Type:

#### Single shaft

Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

### Mounting Method:

Standard bushing

#### **Electrical Resistance Per Section:**

3.500 megohms single section

### Power Dissipation Rating Per Section In Watts:

2.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

### Standard Taper Curve Per Section:

C single section

### **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0