

NSN 5905-00-819-1442 Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-819-1442 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.571 inches

Shaft Style:

Round, slotted **Actuator Type:** Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.157 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

100.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

NSN 5905-00-819-1442

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No