## NSN 5905-00-820-2839

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-820-2839

-500.0/40.0 Electrical Resistance: 909.000 kilohms Resistance Tolerance In Percent: -1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5.0/4105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.464 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Sylve Designator: Axial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '*, etc.): Shelf Life: Na Unit of Measure: Demilitarization: No Flig: A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -1.000/4-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 250.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.640 inches Power Dissipation Rating in Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Avial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, inclusity directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure:	-500.0/+0.0
Resistance Tolerance in Percent:  -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  250.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter:  0.244 inches Body Length: 0.440 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Axial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Shelf Life: Na Unit Of Measure:  - Demilitarization: No Flig:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 255.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 255.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.840 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Axial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filg:	909.000 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.540 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Axial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.640 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Axial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Flig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Body Diameter: 0.244 inches Body Length: 0.240 inches  Power Dissipation Rating In Watts: 0.250 free air  Special Features: Radiographic inspection  Style Designator: Axial terminal each end Test Data Document: 94756-443-9003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.640 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Axial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheft Life:  Via Unit Of Measure:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.640 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Axial terminal each end Test Data Document: 94756-4443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.640 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Axial terminal each end Test Data Document: 94756-4443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	250.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.640 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Axial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Body Diameter: 0.244 inches Body Length: 0.640 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Radiographic inspection Style Designator: Avial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+105.0
Terminal Type:  Wire lead  Body Diameter:  0.244 inches  Body Length:  0.640 inches  Power Dissipation Rating In Watts:  0.250 free air  Special Features: Radiographic inspection  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Inclosure Method:
Wire lead  Body Diameter:  0.244 inches  Body Length:  0.640 inches  Power Dissipation Rating In Watts:  0.250 free air  Special Features: Radiographic inspection  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Encapsulated
Body Diameter:  0.244 inches  Body Length:  0.640 inches  Power Dissipation Rating In Watts:  0.250 free air  Special Features: Radiographic inspection  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Terminal Type:
0.244 inches  Body Length: 0.640 inches  Power Dissipation Rating In Watts: 0.250 free air  Special Features: Radiographic inspection  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Length:  0.640 inches  Power Dissipation Rating In Watts:  0.250 free air  Special Features: Radiographic inspection  Style Designator: Axial terminal each end  Test Data Document:  94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Body Diameter:
0.640 inches  Power Dissipation Rating In Watts: 0.250 free air  Special Features: Radiographic inspection  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	0.244 inches
Power Dissipation Rating In Watts:  0.250 free air  Special Features: Radiographic inspection  Style Designator: Axial terminal each end  Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Filig:	Body Length:
Special Features: Radiographic inspection Style Designator: Axial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	0.640 inches
Special Features: Radiographic inspection  Style Designator: Axial terminal each end  Test Data Document:  94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fitig:	Power Dissipation Rating In Watts:
Radiographic inspection  Style Designator:  Axial terminal each end  Test Data Document:  94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.250 free air
Style Designator: Axial terminal each end Test Data Document: 94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Special Features:
Axial terminal each end  Test Data Document:  94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Radiographic inspection
Test Data Document:  94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	94756-443-0003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0