

View Online at <https://aerobasegroup.com/nsn/5905-00-820-4062>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.329 inches

**Body Diameter:**

Between 0.484 inches and 0.516 inches

**Shaft Diameter:**

Between 0.124 inches and 0.126 inches

**Shaft Length:**

Between 0.609 inches and 0.641 inches

**Mounting Bushing Length:**

Between 0.234 inches and 0.266 inches

**Body Length:**

0.453 inches

**Overall Diameter:**

Between 0.484 inches and 0.516 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:**

Between 0.234 inches and 0.266 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Features Provided:**

Shaft seal

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0