

View Online at <https://aerobasegroup.com/nsn/5905-00-820-6102>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.312 inches

**Body Diameter:**

0.500 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.500 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.578 inches

**Overall Diameter:**

0.500 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

360.0

**Nonturn Device Location:**

At 6 oclock

**Nonturn Device Radius:**

0.157 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Locking bushing

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

100.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

165.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0