NSN 5905-00-821-6437

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-821-6437

Section Overther
Section Quantity:
Reliability Indicator:
Not established
Overall Length:
1.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.220 inches
Overall Diameter:
2.000 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.35 inch-ounces
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
75.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
4 single section
Tap Location Tolerance Per Section:

-2.0/+2.0 degrees angular rotation single section

NSN 5905-00-821-6437

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
8 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No