

View Online at <https://aerobasegroup.com/nsn/5905-00-821-8604>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

Between 1.124 inches and 1.436 inches

Body Diameter:

Between 1.500 inches and 1.710 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

Between 0.594 inches and 0.656 inches

Mounting Bushing Length:

Between 0.485 inches and 0.515 inches

Body Length:

Between 0.530 inches and 0.780 inches

Overall Diameter:

2.135 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 280.0 and 305.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.516 inches and 0.546 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

25.0 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 280.0 and 305.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-19/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0