NSN 5905-00-822-3044

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-822-3044 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.370 inches **Overall Height:** 0.360 inches **Overall Width:** 0.300 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** Between 0.109 inches and 0.141 inches **Shaft Length:** 0.030 inches **Body Length:** 1.340 inches **Body Width:** 0.300 inches **Body Height:** 0.360 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 7.50 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity: Terminal Location:** Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

2.0 kilohms single section

NSN 5905-00-822-3044

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
135.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0/+2.0 ohms single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Tap Location From Ccw Terminal Per Section In Ohms:
1000.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No